standard specifications

- Patented Air-Flow contoured shape
- Exclusive Aero-Stress® high-strength steel undercarriage
- Molded steel bumper, welded to undercarriage
- Exclusive super Dura Torque® rubber torsion bar axles
- Shock absorbers on all wheels
- Tandem wheels on 25 foot Trade Wind;
 27 foot Overlander;
 29 foot Ambassador and
 31 foot Sovereign of the Road
- 12 volt electric brakes on all wheels—can be coordinated with foot brake pedal in car
- Automatic electric break-away switch
- 7:00 x 15 Truck-type extra strength wheels with nylon tubeless tires (6 ply on 18 foot Caravel and 21 foot Globetrotter; 8 ply on 23 foot Safari; 6 ply on all tandem axle models)
- Hand-riveted double-shell body of heat treated structural alloy aluminum
- Ribs of stretch-formed structural alloy aluminum
- Exterior protective acrylic coating
- Wear-resistant vinyl surface laminated to metal interior walls
- One-piece aluminum window frames riveted to body
- Exclusive contoured Jet-Seal awning-type safety glass windows
- Corrosion-proof screens in all windows
- Front window guard of transparent Butyrate
- Insulated, unitized door and screen door
- Exclusive touch-control fold-away steel step, welded to frame
- Polished aluminum grab handle
- Trunk compartment with lock and insulated door
- *Rear service area for storage of water line, 110 volt power cord, 12 volt battery and septic tank valve
- *Univolt convenience light in rear service area and trunk
- · Awning rail
- Seamless, dustproof, high impact Styrene wheel housing covers
- Adjustable, no-draft aluminum roof vents
- 2¹/₂ inch aircraft type fiberglass insulation
- · Plastic grip on jack handle
- *Weatherproof exterior 110 volt outlet
- Single plug weatherproof car-trailer connector includes 12 volt charge line (detachable in Deluxe and International Land Yacht Series)
- TV lead-in wire in shell
- Univolt service available at all roof vents
- *Univolt ceiling exhaust fan in bathroom
- Built-in 110 volt service line (25 feet)

- U.S.A.S.I. and D.O.H. Code-approved wiring system
- Interior 110 volt convenience outlets
- Three-position Univolt interior lights (operate on 110 volt or 12 volt current)
- Oversized 90 ampere hour 12 volt battery in vented case
- Battery charger with protective voltage regulator
- *Battery operated clock
- Automatically resetting circuit breakers on Univolt and Univolt wiring system
- Overload safety fuse cartridges on Univolt wiring system
- Circuit breakers on 110 volt wiring system
- Two bulb, corrosion-proof 180° visibility exterior clearance and running lights
- *Back-up lights
- Exterior clearance and running lights and reflectors installed in conformance with the Federal Motor Vehicle Safety Standards
- High volume water pressure regulator in water inlet line
- Univolt marine water pump (capacity 3 gallons per minute)
- 30 Gallon polyethylene water tank
- *Water level gauge
- U.S.A.S.I. and D.O.H. Code approved plumbing system
- *Swing faucet at galley sinks
- *Double stainless steel galley sinks
- *Exclusive all-fibreglass Bel-Air bathroom
- Fibreglass bathtub except in Special Land Yacht Series which has fibreglass shower stall
- Fibreglass lavatory
- Built-in medicine chest and mirror
- Imported water-saver "telephone" shower with shut-off valve
- Marine type toilet
- Toilet hand spray flushing device
- Polyethylene holding tank of approximately one week capacity
- Drainage drop-out cover cap
- Drainage drop-out elbow for connecting sewer hose
- Built-in sewer hose carrier
- All gas equipment U.L. or A.G.A. approved for use in travel trailers
- Double five gallon gas bottles with rack
- U.S.A.S.I. and D.O.H. Code approved gas system
- Sealed unit, side-vented gas space heater (input ratings: 18 foot Caravel, 9,000 B.T.U.; 21 foot Globetrotter, 16,000.B.T.U.; 23 foot Safari, 25 foot Trade Wind and 27 foot Overlander, 22,500 B.T.U.; 29 foot Ambassador and 31 foot Sovereign of the Road, 30,000 B.T.U.)

- Automatic heater thermostat
- *Built-in igniter for space heater
- *Univolt blower and under-the-floor circulating ducts
- Gas/electric combination refrigerator: 3.5 cubic foot in 18 foot Caravel and 21 foot Globetrotter; 5.5 cubic foot in 23 foot Safari, 25 foot Trade Wind and 27 foot Overlander; 7 cubic foot in 29 foot Ambassador and 31 foot Sovereign of the Road
- Gas range with oven and broiler
- Range vent hood
- Ten gallon gas water heater except in the Special Land Yacht Series with 6 gallon gas water heater
- *Built-in igniter on gas water heater
- Genuine hardwood veneer furniture and cabinets (natural ash in Special and Deluxe Land Yacht Series ... American walnut in International Land Yacht Series)
- Lightweight, warp-free hollow core wardrobe doors
- Travel-sure locks on all roof locker doors and cabinet doors
- Drawers of lightweight molded high-impact Styrene
- Variable storage for all drawer areas (can be used for drawers, as shelves or as open storage)
- Silverware drawer
- Credenza fold-away table with built-in extension leaf (except in 21 foot Globetrotter, 23 foot Safari Twin and 25 foot Trade Wind Twin with pull-out table)
- Foam travel lounge in front, convertible to double bed (except in 21 foot Globetrotter, 23 foot Safari Twin and 25 foot Trade Wind Twin with twin lounge beds in front)
- 6" foam mattresses with zippered covers (except in Special Land Yacht Series which has 4" foam mattresses with zippered covers)
- All upholstery treated with SCOTCHGARD repeller to resist soiling
- All curtains fade resistant and pre-shrunk
- *All curtains lined
- Decorator-styled, washable vinyl window shades at galley and bathroom windows
- Full-length mirror
- *Regency hollow core bathroom door
- Bedroom vinyl folding door in 25 foot double bed models and longer
- · Vinvl floor tile
- Outside floor width . . . 7' 8"
- Outside height from ground...8' 10"
- Inside height (floor to ceiling) . . . 6' 7"
- Ground clearance ... 16" to underbelly, 12.24" to axle tube
- Recommended hitch ball height...19"