



## STANDARD SPECIFICATIONS

### BASIC CONSTRUCTION:

- Patented Air-Flow contoured shape
- Exclusive Aero-Stress® high-strength steel undercarriage
- \*Extrusion-formed aluminum bumper bolted to undercarriage
- Exclusive super Dura-Torque® rubber torsion bar axles
- Shock absorbers on all wheels
- Tandem wheels on models 25' and longer (optional on 23' Safari)
- 12 volt electric brakes on all wheels — can be coordinated with foot brake pedal in car
- 7:00 x 15 Truck-type extra strength wheels with nylon tubeless tires (6 ply on 18' Caravel and 21' Globetrotter; 8 ply on 23' Safari; 6 ply on all tandem axle models)
- Hand riveted double-shell body of heat treated structural alloy aluminum
- Ribs of stretch-formed structural alloy aluminum
- Interior walls of wear-resistant vinyl laminated to aluminum

- One-piece aluminum window frames riveted to body
- Exterior protective acrylic coating
- Exclusive contoured Jet-Seal awning-type safety glass windows
- Corrosion-proof screens in all windows
- Front window guard of transparent Butyrate
- Insulated, unitized door and screen door
- Exclusive touch-control fold-away steel step, welded to frame
- Trunk compartment with lock and insulated door (except in 18' Caravel and 21' Globetrotter)
- \*Rear service area for storage of water line, 110 volt power cord, 12 volt battery and septic tank valve
- \*Univolt convenience light in rear service area and trunk
- Awning rail
- Seamless, dustproof, one-piece polyethylene wheel housings
- Adjustable, no-draft aluminum roof vents
- 2½ inch aircraft type fibreglass insulation

### ELECTRICAL EQUIPMENT:

- †A.N.S.I. and D.O.H. and C.S.A. Code-approved wiring system
- Detachable single-plug weatherproof car-trailer connector (includes 12 volt charge line)

- Two-bulb, corrosion-proof 180° visibility exterior clearance and running lights
- Automatic electric break-away switch
- Exterior clearance and running lights and reflectors installed in conformance with Federal Motor Vehicle Safety Standards
- Back-up lights
- Weather-proof exterior 110 volt outlet
- Built-in 110 volt service line (25 feet)
- Extra-capacity 100 ampere hour 12 volt battery in vented case
- Battery charger with protective voltage regulator
- Univolt ceiling exhaust fan in bathroom
- Three-position Univolt interior lights (operate on 110 volt or 12 volt current)
- Interior 110 volt convenience outlets
- Automatically resetting circuit breaker on Univolt
- Overload safety fuse cartridges on Univolt wiring system
- Circuit breakers on 110 volt wiring system

### PLUMBING:

- †A.N.S.I. and D.O.H. and C.S.A. Code-approved plumbing system
- High volume water pressure regulator in water inlet line
- Univolt marine water pump (capacity 3 gallons per minute)





30 Gallon polyethylene water tank  
 Running faucet at double galley sinks  
 Stainless steel galley sinks  
 Exclusive all-fiberglass Bel-Air bathroom with thermo-formed bathtub except in Land Yacht series which has thermo-formed shower room  
 Thermo-formed lavatory  
 Built-in medicine chest and mirror  
 Imported water-saver "telephone" shower  
 Marine-type toilet  
 Polyethylene holding tank of approximately one week capacity  
 Drainage drop-out cover cap  
 Drainage drop-out elbow for connecting sewer hose  
 Built-in sewer hose carrier

**AS EQUIPMENT:**

A.N.S.I. and D.O.H. and C.S.A. Code-approved gas system  
 All gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers  
 Double five gallon gas bottles with rack  
 Sealed unit, side-vented gas space heater (input ratings: 18' Caravel and 21' Globetrotter, 16,500 B.T.U.; 23' Safari, 25' Trade Wind and Caravanner and 27' Overlander, 22,500 B.T.U.; 29' Ambassador and 31' Sovereign of the Road, 30,000 B.T.U.)

- Automatic heater thermostat
- Built-in igniter for space heater
- Univolt blower and circulating ducts
- Gas/electric combination refrigerator: 4.0 cubic foot in 18' Caravel and 21' Globetrotter; 6 cubic foot in 23' Safari, 25' Trade Wind and Caravanner and 27' Overlander; 7½ cubic foot in 29' Ambassador and 31' Sovereign of the Road
- Gas range with oven and broiler
- Range vent hood
- Ten gallon gas water heater except in the Land Yacht series with 6 gallon gas water heater
- Built-in igniter on gas water heater

**FURNISHINGS:**

- Exclusive, new Perma-Tech® furniture construction featuring heat-treated, anodized aluminum framework with textured high-pressure laminate panels
- Lightweight warp-free hollow core doors
- Roll-away cabinet and roof locker doors
- Travel-sure locks on all cabinet doors
- Drawers of lightweight high-impact Styrene
- Silverware drawer
- Credenza fold-away table in all models with front travel lounge
- Six inch foam mattresses in bedroom with zippered covers

- Carpeting in all areas. Nylon in Land Yacht Series; Kodel in International Land Yacht series
- All upholstery treated with SCOTCHGARD repeller to resist soiling
- All draperies fade resistant and pre-shrunk
- All draperies lined
- Decorator-styled, washable vinyl window shades at galley and bathroom windows
- \*Full length mirror
- \*Slide-away bathroom door
- Bedroom vinyl folding door in 23' models and longer

**DIMENSIONS:**

- Outside floor width . . . 7' 8"
- Outside height from ground . . . 8' 10"
- Inside height (floor to ceiling) . . . 6' 7"
- Ground clearance . . . 16" to underbelly, 12.24" to axle tube
- Recommended hitch ball height . . . 19"

\* Not included in Land Yacht series  
 † American National Standards Institute . . . California Division of Housing . . . Canadian Standards Association

All specifications subject to change without notice