# ARGOSY standard specifications

#### CHASSIS

- Chevrolet Motorhome chassis, 350 or 454 V8 engine (454 standard on 28' models).
- Front suspension providing passengercar-type handling with reinforced control arms, crossmember, stronger control arm shaft and auxiliary air springs.
- New Firestone "Air Ride Suspension System" on 28" models.
- Front disc brakes and rear drum brakes with improved brake lining material.
- High-ratio brake pedal for reduced pedal effort.
- · Frame-mounted master cylinder.
- Hydro-Boost brake system using hydraulic pressure from power steering pump providing passenger-car-type performance.
- · In-line cannister-type fuel filter.
- · Gauge-type instrument cluster.
- Turbo Hydramatic 3-speed transmission.
- · Power steering with tilt column.
- · 80 amp hour battery.
- · 61 amp Delcotron generator.
- · Dual rear wheels, all models.
- Hydraulic jack and tire tools.
- Insulated wheel wells with sound retardant covering.
- Recirculating air heater, separate blower, separate passenger control.
- Outside access to engine water fill, oil fill, windshield washer fluid and batteries.
- Electric windshield wipers and washers.
- · Blade-mounted windshield washers.
- Fire extinguisher.
- · Emergency warning triangle.
- · Headlight warning system.
- · Rear end stabilizer.

#### DRIVER'S COMPARTMENT

- · Padded dash.
- · Arm rests, both sides, both seats.

- · Built-in headrests.
- · Cigarette lighter.
- · Ash trays.
- · Inside rear-view mirror.
- · Twin outside rear-view mirrors.
- Super panoramic laminated safety glass tinted windshield with sunband.
- Deluxe contoured swivel seats for driver and passenger; extra back and seat cushioning on driver's seat.
- Dash-mounted step, aisle, map, and trunk light controls.
- Dash-mounted door-open lights and step-down lights.

# BASIC SHELL CONSTRUCTION

- Semi-monocoque air flow aerodynamic shape.
- · Extruded aluminum bumpers.
- · Rectangular dual headlights.
- Hand-riveted shell of structural alloy aluminum.
- Exterior painting of automotive acrylic
- Ribs of stretch-formed structural alloy aluminum.
- Cab frame of structural alloy aluminum with heavy-duty aluminum extruded roll bar.
- Interior walls of wear-resistant vinyl laminated to aluminum.
- One-piece, stretch-formed extruded aluminum window frames riveted to body.
- Exclusive contoured sliding and fixed windows of Herculite safety glass.
- Exclusive touch control aluminum fold-away entrance step.
- · Awning rail.
- 2¼ -inch aircraft-type fiberglass insulation.
- Adjustable no-draft aluminum roof yents.
- · Outside storage areas.
- Super panoramic rear windows of Herculite safety glass (side-bath models).

- · Screen door.
- · Security lock.

### **ELECTRIC EQUIPMENT**

- A.N.S.I. ("R.V.I.A.") and D.O.H. code approved wiring system.
- Built-in 110V service line extends 20 feet.
- 80 amp hour battery for living area with automotive charging when driving or Univolt charging when plugged into 120V city power or when 120V optional power plant is in operation.
- · Univolt ceiling lights.
- Ferro resonant Univolt to convert 110V city power to 12V direct current power.
- Overload safety fuse cartridges on Univolt wiring system.
- Circuit breakers on 110V wiring system.
- Sealed and vented battery compartment.
- Ground fault interrupter for bathroom and exterior outlets.

# PLUMBING

- A.N.S.I. ("R.V.I.A.") and D.O.H. code approved plumbing system.
- · Lockable water fill.
- Univolt demand pump (3 gallons per minute).
- Water tank capacities: 50 gallons for 28' rear bath models; 35 gallons for 24' and 20' models.
- Swing faucet and double stainless steel galley sinks.
- Exclusive all-thermo-formed bathroom with sit-down shower stall.
- Pullman lavatory.
- Polyethylene holding tanks for black and grey water.
- · City water inlet hook-up.
- · Built-in medicine chest and mirror.
- · Water saver "telephone" shower head.
- · Mechanically sealed flush toilet.

 Drainage drop-out cover cap with all-plastic drain valve for each tank.



# L.P. GAS EQUIPMENT

- A.N.S.I. ("R.V.I.A.") and D.O.H. code approved gas system.
- Sealed outside vent, automatic ignition, forced air gas furnace with heat ducts. Input rating: 22,000 BTU 20'; 30,000 BTU 24' and 28'.
- Gas/Electric combination refrigerator (20' — 6 cubic ft.; 24' and 28' — 10 cubic ft.).
- 50 lb. frame-mounted LPG gas bottle with Safety Overfill Valve.
- Automatic heater wall thermostat.
- · Gas range with oven and broiler.
- · Range vent exhaust hood.
- Fast-recovery six-gallon water heater.

#### **FURNISHINGS**

 Exclusive furniture construction of new vinyl clad aluminum.

- Lightweight, warp-free hollow core doors.
- · PosiLock latches on all cabinet doors.
- Under-bed storage with drawers of lightweight high-impact styrene.
- · Silverware drawer.
- Foam mattresses for all upholstery with zipped covers.
- Roll-a-way doors in all rear bath models.
- · Spice rack.
- Beverage bottle storage in 24' and 28' models.
- Lightweight injection molded galley and vanity drawers.
- Roomy wardrobes in all models.
- Spacious storage lockers.
- · Color-coordinated interiors.
- Easy roll-up tambour doors on all cabinets.
- Exclusive "Feather Touch" one-piece 5th Avenue Convertible Lounge-Bed (28' models).

- All upholstery is treated with Scotch-Gard repeller to resist soiling.
- · Plush shag nylon carpeting with pad.
- All draperies fade-resistant lined and pre-shrunk.
- Decorator style washable vinyl window shades at galley and bathroom windows.
- All materials meet applicable flammability specifications.
- Twin bed bolster backs upholstered (2).

#### **DIMENSIONS**

- Outside height (with air conditioner): 20' and 24' models, 10'; 28' model, 10'2".
- · Inside height, floor to ceiling: 6'7".
- Ground clearance: 20' and 24' models, 13" to underbelly, 7" to differential low point; 28' model, 14½" to underbelly, 9" to differential low point.

# optional equipment



## **EXECUTIVE GROUP**

- 50 gallon fuel tank (standard on 28', optional on 24', not available on 20').
- · Hitch platform.
- · Automotive air conditioner.

#### CONVENIENCE GROUP

- · Univolt ceiling exhaust fan.
- Univolt bath exhaust fan.
- · Univolt stove exhaust fan.
- Solid state central control and monitoring system.
- · Entrance light.
- · Compartment lights.
- Combination sink covers and cutting boards.
- · Toilet water saver spray.\*

#### **DELUXE GROUP**

- · Solardome.\*
- · Deluxe wheel covers.
- · Cruise control.
- · Outside flood light.
- · Vacuumatic step.\*

#### ENTERTAINMENT GROUP

- Built-in stereo AM/FM radio,
  4-speakers, w/8 track stereo tape deck, with or without CB radio.
- TV antenna, UHF, VHF, and color adapter, includes TV jack with 12V outlet.
- · Telescoping radio antenna.

#### **GENERAL OPTIONS**

- Bolster bunk beds 60" in rear bath twin models.
- · Main door window.
- · Radial tires.\*
- · C.B. antenna.
- · Privacy curtition (24' only).
- Driver and passenger reclining seats.\*
- Roof air conditioner (12,000 BTU on 20' and 24' models; 14,000 BTU on 28' models).
- Step extension (not available with power step).
- 5th Avenue Convertible Lounge-Bed.
- Canadian standards association code approvals.

- Deluxe AM/FM stereo and 8-track stereo tape deck with 4 speakers.
- · Ice maker (28' only).
- · Converta-Lux Lounge (20' only).\*
- Fuel vapor emission controls (required on Calif. motorhomes).
- · Spare wheel, tire, carrier, and cover.
- Nutone food center (24' and 28' models).
- · Water filter.
- · Central vacuum cleaner.
- · Adjustable towel rack.
- 120V generator, 4000W (Onan).
- · 454 engine (standard on 28' model).\*
- 65 lbs. propane tank (24' and 28' only).\*
- · Front and rear bumper guards.
- \*Denotes exchange for standard equipment.

All specifications and prices are based on the latest product information available at the time of publication. The right is reserved to make changes at any time in prices, colors, material, equipment; specifications, and models, and also to discontinue or add models.

