

# ARGOSY 1978

## MINUET STANDARD SPECIFICATIONS

### BASIC CONSTRUCTION

- Patented Air-Flow contoured shape.
- Inert gas electro-welded high-strength steel undercarriage.
- Dura-Torque rubber torsion bar axles.
- Shock absorbers on all wheels.
- 12 volt electric brakes on all wheels—can be coordinated with foot brake pedal in car.
- 15" truck type extra strength wheels.
- Hand riveted monocoque shell.
- Exterior protection: Automotive type acrylic enamel.
- Ribs of stretch-formed structural alloy aluminum.
- Interior walls of wear-resistant vinyl covered aluminum.
- One piece stretch-formed extruded aluminum window frames riveted to body.
- Exclusive contoured Jet-Seal awning-type Acrylic side windows.
- Panoramic front windows using super strength Herculite safety glass.
- Corrosion proof screens in all windows.
- Awning rail.
- Double walled fiberglass insulated wheel wells.
- 2 ¼ inch aircraft type fiberglass insulation.
- Adjustable no draft aluminum roof vents.
- Custom steel wheels.

### ELECTRICAL EQUIPMENT

- A.N.S.I., D.O.H., C.S.A. (optional) and N.E.C. code approved wiring system.
- Single plug weatherproof car trailer connector (includes 12 volt charge line).
- One bulb, corrosion proof 180° visibility exterior clearance and running lights (installed in conformance with Federal Motor Vehicle Safety Standard 108).
- Automatic electric break-away switch.
- Built in 110 volt service line.

- Extra capacity 72 amperes hour 12 volt battery; built in sealed and vented battery compartment.
- Three position Univolt 4 bulb ceiling lights.
- One knob variable position ceiling vents.
- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery.
- Overload safety fuse cartridges in Univolt wiring system.
- Circuit breakers on 110 volt wiring system.
- Polarity warning light.
- Ground fault circuit breaker.

### PLUMBING

- A.N.S.I., D.O.H. and C.S.A. (optional) code approved plumbing system.
- High volume water pressure regulator in water inlet line.
- Univolt water pump.
- 25 gallon polyethylene water tank.
- Swing faucet at galley sinks.
- Stainless steel galley sinks.
- Exclusive all thermo formed bathroom with shower room.
- Built in medicine chest and mirror.
- Telephone shower head.
- Mechanical seal toilet.
- Polyethylene holding tanks.
- Drainage drop out cover cap.
- Drainage drop out elbow for connecting sewer hose.
- Built in sewer hose carrier.
- Accessible dump valve.
- Lockable, flush water fill.
- Polyethylene fresh water system.

### GAS EQUIPMENT

- A.N.S.I., D.O.H. and C.S.A. (optional) code approved gas system.
- All gas equipment U.L. or A.G.A. and C.S.A. (optional) approved for use in travel trailers.

- Double five gallon aluminum gas bottles with rack.
- Sealed outside vented heater (input ratings: 16,000 BTU).
- Automatic heater thermostat.
- Univolt sealed combustion system with forced air circulating ducts.
- Gas/electric combination refrigerator: 4.5 cubic foot.
- Gas range with oven and broiler.
- Range vent hood.
- 6 gallon gas water heater.

### FURNISHINGS

- Exclusive vinyl covered aluminum furniture.
- Tambour doors in all roof lockers.
- Tambour galley door.
- Posi-Lok latches on all hinged doors.
- Lightweight injection molded drawers.
- Credenza table in all models with front travel lounge.
- Nylon shag carpet in all areas.
- All upholstery treated with SCOTCH-GARD repeller to resist soiling.
- All draperies fade resistant.
- Decorator styled washable vinyl window shades at galley and bathroom windows.
- Lined drapes.
- Foldette bathroom door.
- Choice of four color schemes.
- Fire extinguisher.

### DIMENSIONS

- Outside floor width . . . 7'0".
- Outside height from ground . . . 8'5½".
- Inside height (floor to ceiling) . . . 6'4".
- Ground clearance . . . 16" to underbelly. 12" to axle tube.
- Recommended hitch ball height . . . 18".
- All specifications subject to change without notice.