

# ARGOSY 1978

## STANDARD SPECIFICATIONS FOR 24, 27, 30 FT. MODELS

### BASIC CONSTRUCTION

- Patented Air-Flow contoured shape.
- Inert gas electro-welded high-strength steel undercarriage.
- Dura-Torque rubber torsion bar axles.
- Shock absorbers on all wheels.
- Tandem wheels on 24', 27', and 30'.
- 12 volt electric brakes on all wheels — can be coordinated with foot brake pedal in car.
- 15" truck type extra strength wheels with 7:00 x 15 nylon tubeless tires (C-rated on double axle models).
- Hand riveted semi-monocoque shell.
- Exterior protection: Automotive type acrylic enamel.
- Ribs of stretch-formed structural alloy aluminum.
- Interior walls of wear-resistant vinyl covered aluminum.
- One piece stretch-formed extruded aluminum window frames riveted to body.
- Exclusive contoured Jet-Seal awning-type Herculite safety glass windows.
- Panoramic front windows using super strength Herculite safety glass.
- Corrosion proof screens in all windows.
- Exclusive touch control fold away aluminum entrance step.
- Awning rail.
- Double walled fiberglass insulated wheel wells.
- 2 ¼ inch aircraft type fiberglass insulation.
- Adjustable no draft aluminum roof vents.
- Custom steel wheels.

### ELECTRICAL EQUIPMENT

- A.N.S.I., D.O.H., C.S.A. (optional) and N.E.C. code approved wiring system.
- Single plug weatherproof car trailer connector (includes 12 volt charge line).
- One bulb, corrosion proof 180° visibility exterior clearance and running lights (installed in conformance with Federal Motor Vehicle Safety Standard 108).
- Automatic electric break-away switch.
- Back up lights.
- Interior light switch at door.
- Built in 110 volt service line.

- Extra capacity 72 amperes hour 12 volt battery; built in sealed and vented battery compartment.
- Three position Univolt 4 bulb ceiling lights.
- One knob variable position ceiling vents.
- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery.
- Overload safety fuse cartridges in Univolt wiring system.
- High intensity adjustable reading lights.
- Circuit breakers on 110 volt wiring system.
- Polarity warning light.

### PLUMBING

- A.N.S.I., D.O.H. and C.S.A. (optional) code approved plumbing system.
- High volume water pressure regulator in water inlet line.
- Univolt water pump.
- 30 gallon polyethylene water tank.
- Swing faucet at galley sinks.
- Stainless steel galley sinks.
- Exclusive all thermo formed bathroom with bathtub in rear bath, shower room in 24' and 30' center bath.
- Built in medicine chest and mirror.
- Telephone shower head.
- Mechanical seal toilet.
- Polyethylene holding tanks.
- Drainage drop out cover cap.
- Drainage drop out elbow for connecting sewer hose.
- Built in sewer hose carrier.
- Accessible dump valve.
- Lockable, flush water fill.
- Polybutylene water lines.

### GAS EQUIPMENT

- A.N.S.I., D.O.H. and C.S.A. (optional) code approved gas system.
- All gas equipment U.L. or A.G.A. and C.S.A. (optional) approved for use in travel trailers.
- Double five gallon gas bottles with rack.
- Sealed outside vented heater (input ratings: 24' and 27' = 22,000 BTU and 30' = 30,000 BTU).

- Automatic heater thermostat.
- Univolt sealed combustion system with forced air circulating ducts.
- Gas/electric combination refrigerator: 6.0 cubic foot in 24', 27' and 30'.
- Gas range with oven and broiler.
- Range vent hood.
- 6 gallon gas water heater.

### FURNISHINGS

- Exclusive Perma-Tech furniture construction featuring heat treated anodized aluminum framework with textured vinyl panels.
- Lightweight warp free hollowcore doors.
- Tambour doors in all roof lockers.
- Tambour cabinet doors.
- Posi-Lok latches on all cabinet doors.
- Lightweight injection molded galley and vanity drawers.
- Credenza table in all models with front travel lounge.
- Bedroom wall comfort covers.
- Foam mattresses in bedroom with zippered covers.
- Nylon plush carpet.
- All upholstery treated with SCOTCHGARD repeller to resist soiling.
- All draperies fade resistant.
- Decorator styled washable vinyl window shades.
- Slide away bathroom door (except 20' Minuet).
- Bedroom vinyl folding door (24', 27' and 30' only).
- Choice of four color schemes.
- Fire extinguisher.

### DIMENSIONS

- Outside floor width . . . 7'8".
- Outside height from ground . . . 8'10".
- Inside height (floor to ceiling) . . . 6'7".
- Ground clearance . . . 16" to underbelly. 12.24" to axle tube.
- Recommended hitch ball height . . . 19 ½".
- All specifications subject to change without notice.