

# STANDARD SPECIFICATIONS

## BASIC CONSTRUCTION:

- Patented Air-Flow contoured shape
- Exclusive Aero-Stress high-strength steel undercarriage
- Extruded aluminum bumper
- Dura-Torque torsion bar axles
- Shock absorbers on all wheels
- Tandem wheels on all models
- Automatic break-away control
- 15" Truck-type extra strength wheels with 7:00 x 15 nylon tubeless tires; C-rated
- Hand riveted semi monocoque shell of heat treated structural alloy aluminum
- Exterior protective acrylic coating
- Ribs of stretch-formed structural alloy aluminum
- Interior walls of wear-resistant vinyl covered aluminum
- One-piece stretch-formed extruded aluminum window frames riveted to body
- Exclusive contoured Jet-Seal awning-type Herculite safety glass windows
- Super strength front window (Herculite safety glass)
- Corrosion-proof screens in all windows
- Exclusive touch-control fold-away aluminum entrance step
- Univolt convenience light in rear service area and side trunk area
- Awning rail
- Double-walled fiberglass insulated wheel wells
- 2¼ inch aircraft type fiberglass insulation
- Adjustable, no-draft aluminum roof vents

## ELECTRICAL EQUIPMENT:

- A.N.S.I., D.O.H., C.S.A. (optional) and N.E.C. Code-approved wiring system
- Detachable single-plug weatherproofed car-trailer connector (includes 12 volt charge line)
- Two-bulb, corrosion-proof 180° visibility exterior clearance and running lights (installed in conformance with Federal Motor Vehicle Safety Standard 108)
- Back-up lights
- Built-in 110 volt service line
- Extra-capacity 105 ampere hour 12 volt battery in built-in, sealed and vented battery compartment
- 120 volt exterior patio outlet
- Exclusive exterior electrical duplex outlet
- Three-position Univolt ceiling lights combined with ceiling vents
- Exclusive, one knob variable position ceiling vents

- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery
- Overload safety fuse coded panel in Univolt wiring system
- Circuit breakers on 110 volt wiring system
- Interior light switch at door
- Switch center in bathroom

## PLUMBING:

- A.N.S.I., D.O.H. and C.S.A. (optional) Code-approved plumbing system
- High volume water pressure regulator in water inlet line
- Lockable, flush water fill
- Univolt demand pump (capacity 3 gallons per minute)
- 50 Gallon polyethylene water tank between axles
- Swing faucet at double galley sinks
- Stainless steel galley sinks
- Exclusive all thermo-formed bathroom with bathtub in 25-foot Caravanner, 28 and 31-foot models. Stall shower in 23, 25, and 31-foot center bath models
- Built-in medicine cabinet and mirror
- Panoramic roof lockers with mirror doors in full bath models
- Large pullman lavatory
- Clothes hamper and bag (Full bath only)
- Make-up lighting
- Water-saver "telephone" shower head
- Mechanical seal, flush toilet
- Polyethylene holding tanks of approximately one week capacity
- Drainage drop-out cover cap
- Drainage drop-out elbow for connecting sewer hose
- Built-in sewer hose carrier

## GAS EQUIPMENT:

- A.N.S.I., D.O.H. and C.S.A. (optional) Code-approved gas system
- All gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers
- Double 7 gallon gas bottles
- Sealed, outside vented, forced air gas space heater (Input ratings: 23' Safari and 25' Tradewind, 22,000 B.T.U.; 28' Ambassador and 31' Sovereign of the Road, 30,000 B.T.U.)
- Automatic heater thermostat
- Automatic igniter for space heater
- Univolt blower and circulating ducts

- Gas/electric combination refrigerator: 6 cubic foot in 23' Safari, 25' Tradewind. All other models, 10 cubic feet
- Gas range with oven and broiler
- Range vent hood
- Adjustable exhaust vent
- 'Super 6' water heater on all models
- Built-in igniter on gas water heater

## FURNISHINGS:

- Exclusive all new Perma-Tech II furniture construction featuring heat-treated, color-anodized aluminum framework with textured high-pressure laminate panels
- Lightweight warp-free honeycomb core doors
- Tambour cabinet and roof locker doors
- Posi-Lok latches on all cabinet doors
- Bed drawers of lightweight high-impact styrene
- Lightweight injection molded galley and vanity drawers
- Silverware drawer
- Credenza fold-away table in all models
- Six inch foam fixed mattresses in bedroom with zippered covers
- Nylon plush carpeting
- All upholstery treated with SCOTCHGARD repeller to resist soiling
- Folding chair storage area in 28' and 31'
- All draperies fade resistant
- All draperies lined
- High cube galley storage
- Decorator-styled, washable vinyl window shades at galley and bathroom windows
- Tambour spice rack
- Full length mirror
- Galley flip-up shelf (except 23' side lounge)
- Slide-away bathroom door
- Four color schemes
- Bedroom vinyl folding door in 25', 28' and 31' models
- Exclusive 'feather touch' one piece 5th Avenue lounge

## DIMENSIONS:

- Outside floor width . . . 7'8"
- Outside height from ground . . . 8'10"
- Inside height (floor to ceiling) . . . 6'7"
- Ground clearance . . . 16" to underbelly, 12.24" to axle tube
- Recommended hitch ball height . . . 19½"

*All prices and specifications are subject to change without notice. Standard specifications and prices may vary outside the U.S. to meet local regulations.*