

General Specifications

DESCRIPTION	290	325	345
Chassis (Chevrolet)			
Wheel Base			
Drive	198"	198"	204"
Tag	—	238"	244"
GVWR	14,500#	16,500#	16,500#
ASW*	12,300#	14,000#	14,300#
Tag Axle	—	Henschen Dura-Torque	
Engine Type			
Chevrolet 454 C.I.D.	Gasoline Automotive Engine		
Axle			
Ratio	4.56:1		
Capacities			
Water	60 gal.	60 gal.	80 gal.
Hot Water	6 gal.	6 gal.	6 gal.
Grey Water	28 gal.	43 gal.	43 gal.
Black Water	25 gal.	45 gal.	45 gal.
Fuel Tank	60 gal.	80 gal.	80 gal.
LPG Tank	100#	125#	125#
Dimensions			
Length	29'9 3/4"	32'8"	34'5"
Width	7'11 1/2"	7'11 1/2"	7'11 1/2"
Height Interior	6'6"	6'6"	6'6"
Height Exterior	w/Air 10'6"		
Rear Overhang ¹	116"	120"	133"
Sleeping Area			
Twin Bed	34" x 75"		
Corner Double Bed	54" x 75"		
Convertible Couch	48" x 72"		
Dinette	38" x 72"		
Short Queen Bed	60" x 75"		

*Approximate Standard Weight including fuel (w/o water).
Optional equipment may increase weight.
¹Rear Axle to Bumper Guard.

Chassis Specifications

DESCRIPTION	SPECIFICATION
Engine	
Type	Chevrolet P31832 7.4 Liter, 454, 4-bbl. V-8 7.9:1 Compression Ratio
Oil Cooler	Standard Chevrolet
Exhaust System	Dual; Aluminized
Gasoline	Regular
SAE Net H.P.	230 ¹ @ 3800 RPM @ 77°F
SAE Net Torque	360 ¹ lbs.-ft. @ 2800 RPM @ 77°F
Suspension	
Front	Independent/Positrim — Heavy Duty
Type	Coil Springs with Auxiliary Air Springs
Capacity	5000#
Springs @ ground	2500# ea.
Shock Absorbers	35mm dia.
Stabilizer Bar	1.25" dia.
Rear	Salisbury Axle, Hypoid Drive
Type	Weight Compensating, Self-Leveling Air Spring
Drive Axle Capacity	10,000#
Drive Axle Ratio	4.56:1
Stabilizer Bar	1.75" dia.
Brakes	
Type	Hydraulic, Self-adjusting
Front	Internally-vented Disc; 14.25" Rotor
Rear Drive	Internally-vented Disc; 13.75" Rotor
Rear Tag	Electric - 12" x 2"
Electrical	
Type	12 Volt; Negative ground
Battery — Freedom Type	515 CCA ² @ 0°F
Reserve Capacity	115 min. @ 80°F
Delcotron Generator	100 amps
Frame	
Type	Carbon Steel; 36-39,000 psi Channel Frame Rail
Steering	
Type	Integral Power
Steering Ratio	14:1/3.4 turns, lock to lock
Steering Wheel	Leather padded, 6 position comfortilt
Transmission	
Type	3-Speed Automatic
Oil Cooler	Standard; Integral w/radiator
Tires	
Type	Tubeless, Steel-Belted Radial
Front	8-19.5 (8-ply rating)
Rear	8-19.5 (8-ply rating) Dual
Spare	(1) 8-19.5 (8-ply rating)
Wheels	
Type	19.5" x 6.0"

¹ex. California
²CCA — Cold Cranking Amps