

Optional Features CONT'D.

DESCRIPTION	290	325	345
Decor Lounge			
Road Side Deluxe Lounge w/3 - Seat Belts, Above Floor Access Door, Pedestal Table	0	N/A	N/A
Lift Up Table w/2 Cocktail Chairs with Seat Belts, Pedestal Table (No TV)	N/A	0	N/A
Appliances			
4-Burner Range w/Oven (Delete Pan Storage)	0	0	0
Nutone Food Center	0	S	S
Ice maker In Lieu of (3) Pantry Drawers	N/A	0	0
Ice Maker In TV Cabinet	0	N/A	N/A
Vacuum Cleaner (Portable)	0	S	S
Insta-Hot Water Tap	0	0	S
TV Antenna w/Lift, Telephone & Cable Hook-Up	S	S	S
Built-In 12V/110V Color TV	0	S	S
2nd TV w/Swivel (Bedroom)	N/A	N/A	0
Video Cassette Recorder	N/A	0	S
Electrical			
Electric Cord Reel	0	S	S
Systems - LPG - Water - Waste			
Floor Safe	0	0	S

NOTE: All Standard and Optional features are available at time of printing. Airstream, however, reserves the right to improve and/or modify the product which may change the features and specifications. Check with your Airstream dealer for updated information and availability.

General Specifications

DESCRIPTION	290	325	345
Chassis (Chevrolet)			
Wheel Base	198"	198"	204"
Drive Tag	—	238"	244"
GVWR	14,500#	16,500#	16,500#
ASW*	12,300#	14,000#	14,300#
Tag Axle	—	Henschen Dura-Torque	
Engine Type			
Chevrolet 454 C.I.D.	Gasoline Automotive Engine		
Axle			
Ratio	4.56:1		
Capacities			
Water	60 gal.	60 gal.	80 gal.
Hot Water	6 gal.	6 gal.	6 gal.
Grey Water	28 gal.	43 gal.	43 gal.
Black Water	25 gal.	45 gal.	45 gal.
Fuel Tank	60 gal.	80 gal.	80 gal.
LPG Tank	100#	125#	125#
Dimensions			
Length	29'9¾"	32'8"	34'5"
Width	7'11½"	7'11½"	7'11½"
Height Interior	6'6"	6'6"	6'6"
Height Exterior	w/Air 10'6"		
Rear Overhang ¹	116"	120"	133"
Sleeping Area			
Twin Bed	34" x 75"		
Corner Double Bed	54" x 75"		
Convertible Couch	48" x 72"		
Dinette	38" x 72"		
Short Queen Bed	60" x 75"		

*Approximate Standard Weight including fuel (w/o water).
Optional equipment may increase weight.
¹Rear Axle to Bumper Guard.

Chassis Specifications

DESCRIPTION	SPECIFICATION
Engine	
Type	Chevrolet P31832 7.4 Liter, 454, 4-bbl, V-8 7.9:1 Compression Ratio
Oil Cooler	Standard Chevrolet
Exhaust System	Dual; Aluminized
Gasoline	Regular
SAE Net H.P.	230 ¹ @ 3800 RPM @ 77°F
SAE Net Torque	360 ¹ lbs.-ft. @ 2800 RPM @ 77°F
Suspension	
Front	Independent/Positrim — Heavy Duty
Type	Coil Springs with Auxiliary Air Springs
Capacity	5000#
Springs @ ground	2500# ea.
Shock Absorbers	35mm dia.
Stabilizer Bar	1.25" dia.
Rear	Salisbury Axle, Hypoid Drive
Type	Weight Compensating, Self-Leveling Air Spring
Drive Axle Capacity	10,000#
Drive Axle Ratio	4.56:1
Stabilizer Bar	1.75" dia.
Brakes	
Type	Hydraulic, Self-adjusting
Front	Internally-vented Disc; 14.25" Rotor
Rear Drive	Internally-vented Disc; 13.75" Rotor
Rear Tag	Electric - 12" x 2"
Electrical	
Type	12 Volt; Negative ground
Battery — Freedom Type Reserve Capacity	515 CCA ² @ 0°F 115 min. @ 80°F
Delcotron Generator	100 amps
Frame	
Type	Carbon Steel; 36-39,000 psi Channel Frame Rail
Steering	
Type	Integral Power
Steering Ratio	14:1/3.4 turns, lock to lock
Steering Wheel	Leather padded, 6 position comforthilt
Transmission	
Type	3 Speed Automatic
Oil Cooler	Standard; Integral w/radiator
Tires	
Type	Tubeless, Steel-Belted Radial
Front	8-19.5 (8-ply rating)
Rear	8-19.5 (8-ply rating) Dual
Spare	(1) 8-19.5 (8-ply rating)
Wheels	
Type	19.5" x 6.0"

¹ex. California ²CCA — Cold Cranking Amps