AIRSTREAM

TOURING COACHES

INTERSTATE 3500

VALUE, STABILITY,
DURABILITY...AND BETTER
FUEL ECONOMY.

THESE ARE WHAT SET US APART – AND HAVE FOR NEARLY 80 YEARS.

More than 65% of all Airstreams ever built (dating back to 1931) are still in service. This remarkable longevity has resulted in Airstream's equally impressive resale value.

Airstream has been in the class "B" motorhome business since 1988 and has produced motorhomes since 1974. The tradition continues with the Airstream Interstate 3500. The rigid unibody construction combines with a low center of gravity and standard Adaptive Electronic Stability Program (Adaptive/ESP) for a confidence-inspiring ride. Dual rear wheels provide better road handling in addition to increased hauling capability and the Mercedes-Benz® Turbo Diesel engine creates a new level of efficiency.






FEEL AT HOME AWAY FROM HOME

No matter how far you travel, the Interstate 3500 surrounds you with all the amenities of home. The galley features a 1.2 cubic foot combination convection/microwave oven for quick convenience anywhere. A stainless steel two-burner cooktop is flush mounted under a designer glass cover. The robust 3.1 cubic foot refrigerator uses an AC/DC compressor that uses 90% less power than standard models.

The Interstate 3500 also boasts a host of additional optional features well beyond others in its class, offering exceptional safety, comfort and control.

- Rear back-up camera with 5.5-inch LCD screen
- 19-inch flat panel LCD TV/DVD
- Roof-mounted 13,500 BTU high-efficiency Carrier[®] air conditioning unit
- Onan® 2.5 KW propane powered generator
- · Manual or automatic awning








AIRSTREAM

TOURING COACHES

| CHASSIS | | |
|--|--------|--------|
| 3500 DAIMLER CHRYSLER SPRINTER VAN | | |
| UNIBODY CONSTRUCTION | STD | STD |
| MERCEDES-BENZ® - 3.0 LITER TURBO CHARGED V-6 DIESEL | STD | STD |
| 280 FT/LB @ 1200 – 2400 RPM | | |
| MERCEDES-BENZ® - 5 SPEED AUTOMATIC W/AUTOSTICK | STD | STD |
| GVWR (GROSS VEHICLE WEIGHT RATING) (GAWR-F 4080 GAWR-R 7720) | 11,030 | 11,030 |
| GVWR INCLUDES FLUIDS, OPTIONS AND CARGO. LIQUID CAPACITIES AND | | |
| WEIGHTS ARE APPROXIMATIONS ONLY | | |
| GCWR (GROSS COMBINED WEIGHT RATING) | 15,250 | 15,250 |
| UBW (UNIT BASE WEIGHT) | 8,436 | 7,976 |
| NCC (NET CARRYING CAPACITY) | 2,594 | 3,504 |
| SEATING CAPACITY – TRAVELING | 8 | 3 |
| SLEEPING CAPACITY | 2 | 2 |
| FUEL TANK – GAL | 26.4 | 26.4 |
| HITCH 500 LB TONGUE WEIGHT/5,000 LB TOWING CAPACITY | STD | STD |
| 30 AMP, 110v SERVICE (INCLUDES 30 AMP EMS [ENERGY | STD | STD |
| CONVERTER/INVERTER (45 AMP CHARGER/750W INVERTER) | STD | STD |
| 220 AMP ALTERNATOR | STD | STD |
| | | |
| SYSTEMS-LPG-WATER-WASTE | | |
| L DO TANK W/DEMOTE FILL 475 OAL /44 OAL & 700/ FILL | OTD | OTD |



 EXTERIOR LENGTH
 22'9"
 22'9"
 22'9"

 EXTERIOR WIDTH
 79.7"
 79.7"

 EXTERIOR HEIGHT WITH ANTENNA
 9'7"
 9'7"

 INTERIOR HEAD ROOM
 74 1/4"
 74 1/4"

 INTERIOR WIDTH @ FLOOR
 70"
 70"

DECOR

TAN GREY

SAND PEARL

